

COMMERCIAL NEOPRENE



# Rubber Sheet Roll

## Technical Data Sheet

COLOR	BLACK
SURFACE	SMOOTH
TEMP RANGE	- 20° F TO 212° F
TENSILE	975 PSI
DUROMETER	60A NOMINAL
ELONGATION	275 %
FIRE RATED	NO
UV RATED	MODERATE
CHEMICAL RESISTENT	MODERATE
COMPOSITION	SYNTHETIC

### PSA DATA

THICKNESS	5 MILS
SURFACE	RELEASE LINER ONE SIDE
TEMPERATURE	250° F
COMPOSITION	ACRYLIC
FDA	NO

### Description

Commercial Grade Neoprene is a very common grade of chloroprene material used industry wide for many applications. Com Grade Neo with stands most detergents, mild petroleum and can withstand moderate ozone exposure for a limited amount of time. Neoprene rubber is well suited for applications requiring a stable, resilient rubber for mostly indoor and sheltered environments. Commercial Grade Neo can also be used as a gasket material.

Rubber Sheet Roll Shippensburg, PA 17257

Phone: 866.832.6006

info@rubbersheetroll.com www.rubbersheetroll.com

COMMERCIAL NEOPRENE

All values given are averages based on test samples and the data given is based on what we have determined to be reliable. As results cannot be predicted or guaranteed for any specific set of conditions, each user should make their own determination of these products suitability for their particular application. **Viton®** is a registered trademark of DuPont Performance Elastomers.