



RubberSheetRoll

Technical Data Sheet

COLOR	BLACK
SURFACE	SMOOTH
TEMP RANGE	- 20° F TO 220° F
TENSILE	1500 PSI
DUROMETER	60A NOMINAL
ELONGATION	190%
FIRE RATED	NO
UV RATED	MODERATE
CHEMICAL RESISTENT	MODERATE
COMPOSITION	SYNTHETIC

PSA DATA

THICKNESS	5 MILS
SURFACE	RELEASE LINER ONE SIDE
TEMPERATURE	250° F
COMPOSITION	ACRYLIC
FDA	NO

Description

High Strength Neoprene is highest tensile strength grade of material for the neoprene rubber that we carry. The high strength material is used in applications requiring a material with superior wear resistance and great flexibility at higher temperatures. This material has good ozone exposure for a limited amount of time.

Rubber Sheet Roll Shippensburg, PA 17257

Phone: 866.832.6006

info@rubbersheetroll.com www.rubbersheetroll.com

All values given are averages based on test samples and the data given is based on what we have determined to be reliable. As results cannot be predicted or guaranteed for any specific set of conditions, each user should make their own determination of these products suitability for their particular application. Viton® is a registered trademark of DuPont Performance Elastomers.



www.twitter.com/rubbersheetroll

www.facebook.com/Rubber-Sheet-Roll

