

ActiveSmart™ Technology

ActiveSmart™ technology is the combination of temperature sensors with smart electronics and variable speed fans that create a controlled environment and optimum temperature to keep food fresher longer.

2 SmartTouch™ Control Panel

For easy access, the new SmartTouch™ control panel is placed in the inside front of the fridge. These controls have been designed to be intuitively simple and easy to use.

3 Ultra Slim Water Dispenser

The new slimline water dispenser is now even easier to use – the angled water delivery still means that almost any size or shape of vessel can be filled, while taking up no storage space in your fridge door. The black finish reflects the styling of Fisher & Paykel's family of kitchen appliances.

4 Soft Close Doors

No more slamming fridge doors or having the door left open with soft-close hinges on the French Door Ice & Water models.

G Ice Boost

In Ice & Water models, the icemaker automatically delivers up to 25% more ice each day* into a dedicated bin that can be easily customized to store different volumes.

*compared to current Fisher & Paykel Ice & Water models

6 Humidity Control System

The Humidity Control System together with the cool and consistent temperature delivered by ActiveSmart™ technology creates the perfect microclimate in each produce bin, maintaining fruit and vegetable quality at just the right humidity and temperature level.

Adaptive Defrost

Adaptive defrost means that there is no need for vacation mode settings. Your fridge intelligently selects the best time to defrost based on how it is being used. When you are away it will use less energy as it recognizes lower levels of use and defrosts less often.

Storage Flexibility

Smart refrigerator organization and food preparation are streamlined with best in class features such as flexible shelving, flexible storage options and easy to access bins and trays on full extension runners.

























Counter	Depth	French	Door
---------	-------	--------	------


	Counter Dept	n French Door
Type of appliances	Ice & Water	Standard
Models available	RF201ADUSX4	RF201ADX4
Finish	EZKleen stainless steel flat door Designer handle Concealed hinge	EZKleen stainless steel flat door Designer handle Concealed hinge
Dimensions (excl. handles)	H 70 ¹⁵ / ₃₂ " W 35 ⁷ / ₁ 6" D 27 ³ / ₈ "	H 70 ¹⁵ / ₃₂ " W 35 ⁷ / ₁₆ " D 27 ³ / ₈ "
Capacity		
Refrigerator Freezer Total	14.6 cu.ft. 5.5 cu.ft. 20.1 cu.ft.	14.6 cu.ft. 5.5 cu.ft. 20.1 cu.ft.
Performance		
ActiveSmart™ Technology Frost free freezer Adaptive defrost Humidity control system	•	•
Sabbath mode		
Refrigerator Soft close doors Ultra slim water dispenser Ice boost SmartTouch™ Control Panel Silver prepainted cabinet LED lighting Bottle holders Adjustable Glass shelves Fruit & vegetable bins Half-width door shelf Full-width door shelf Covered door shelf Door alarms Concealed hinge design	• • • • • • 4 3 2 2 2 2 • •	• • • 4 3 2 2 2 2 • •
Freezer Built in ice maker Ice bin and scoop Frost-free freezer Large plastic bin Small plastic bin Fast freeze Bottle Chill Ice cube trays	• • • 1 2 •	• 1 2 • • • 2
Warranty Parts & labour Additional Sealed system	1 year 4 years	1 year 4 years


parts

Pro	duct Dimensions	
A	Height	70 15/32"
В	Width	35 1/16"
©	Depth (excl. handle, incl. evaporator)	27 3/8"
Cal	oinetry Dimensions	
(D)	Inside height of cavity	711/4"
Flu	sh with refrigerator chassis — full door rotation	
E	Inside width	37"
F	Inside depth	24 13/32"
Flu	sh with refrigerator door—full door rotation	
6	Inside width	46 1/16"
H	Inside depth flush to flat door	27 3/8"
Flu	sh with refrigerator door — 90° door rotation	
	Inside width	44 1/32"
I	inside width	44 %32"
(I)	Inside width Inside depth flush to flat door	27 3/8"
<u> </u>		
<u> </u>	Inside depth flush to flat door	
① — Mir ®	Inside depth flush to flat door	273/8"
O O Mir (K) (L)	Inside depth flush to flat door limum Clearances Side clearance	27 3/8"
Mir (k)	Inside depth flush to flat door limum Clearances Side clearance Side clearance - flush with door - full rotation	27 ³ / ₈ " 25/ ₃₂ " 5 ⁵ / ₁₆ "
① — Mir	Inside depth flush to flat door Imum Clearances Side clearance Side clearance - flush with door - full rotation Side clearance - flush with door - 90° rotation	27 ³ / ₈ " 25/ ₃₂ " 5 ⁵ / ₁₆ " 3 ¹⁷ / ₃₂ "
() () () () () () () () () () () () () (Inside depth flush to flat door Imum Clearances Side clearance Side clearance - flush with door - full rotation Side clearance - flush with door - 90° rotation Rear clearance (incl. rear compartment)	27 ³ / ₈ " 25/ ₃₂ " 5 ⁵ / ₁₆ " 3 ¹⁷ / ₃₂ " 3 ¹⁷ / ₃₂ "















Counter	Danth	Erosch	D
Counter	Debin	French	DOOL

Counter Dept	h French Door
Ice & Water	Standard
RF170ADUSX4	RF170ADX4
EZKleen stainless	EZKleen stainless
steel flat door	steel flat door
Designer handle	Designer handle
Concealed hinge	Concealed hinge
H 67 17/32"	H 67 17/32"
W 31 ³ / ₃₂ "	W 313/32"
D 273/8"	D 27 3/8"
12.2 cu.ft.	12.2 cu.ft.
4.7 cu.ft.	4.7 cu.ft.
16.9 cu.ft.	16.9 cu.ft.
•	•
•	•
•	•
•	•
•	•
•	
•	
•	
•	•
•	•
•	•
	2
	3
	2
	2
	2 2
<u> </u>	∠
•	•
•	
•	
•	•
1	1
2	2
•	•
•	•
	2
_	_
1 year	1 year
	Ice & Water RF170ADUSX4 EZKleen stainless steel flat door Designer handle Concealed hinge H 67 17/32" W 31 3/32" D 27 3/6" 12.2 cu.ft. 4.7 cu.ft. 16.9 cu.ft.


4 years


Additional Sealed system

parts


4 years

Pro	oduct Dimenions	
(A)	Height	67 17/32"
В	Width	313/32"
©	Depth (excl. handle, incl. evaporator)	273/8"
Cal	binetry Dimensions	
D	Inside height of cavity	68 5/16"
Flu	sh with refrigerator chassis — full door rotation	
(E)	Inside width	32 11/16"
F	Inside depth	24 13/32
(H)	Inside depth flush to flat door	27%"
Н	Inside depth flush to flat door	27¾"
Flu	sh with refrigerator door — 90 $^\circ$ door rotation	
1	Inside width	39 31/32
<u> </u>	Inside depth flush to flat door	27¾"
Min	ilmum Clearances	
K	Side clearance	25/32"
L	Side clearance - hinge side flush with door - full rotation	5 1/16"
M	Side clearance - hinge side flush with door - 90° rotation	3 17/32"
N	Rear clearance (incl. evaporator tray)	13/16"
0	Vent (above refrigerator cabinet or around top of cupboard)	131/32"
P	Door clearance - hing side flush with chassis - full rotation	12 25/32"
@	Door clearance - hinge side flush with door - full rotation	8 1/32"





Plan View
Flush with refigerator chassis full door rotation












Type of appliances	Ice & Water	Standard
Models available	RF170WDRUX4 RF170WDLUX4	RF170WDRX4 RF170WDLX4
Finish	EZKleen stainless steel flat door Designer handle Concealed hinge	EZKleen stainless steel flat door Designer handle Concealed hinge
Dimensions (excl. handles)	H 67 ¹⁷ / ₃₂ " W 31 ³ / ₃₂ " D 27 ³ / ₈ "	H 67 ¹⁷ / ₃₂ " W 31 ³ / ₃₂ " D 27 ³ / ₈ "
Capacity		
Refrigerator Freezer Total	12.3 cu.ft. 4.7 cu.ft. 17.0 cu.ft.	12.3 cu.ft. 4.7 cu.ft. 17.0 cu.ft
Performance		
ActiveSmart™ Technology Frost free freezer Adaptive defrost Humidity control system	•	•
Sabbath mode	•	•
Refrigerator Ultra slim water dispenser lee boost SmartTouch™ Control Panel Silver prepainted cabinet LED lighting Bottle holders Adjustable Glass shelves Fruit & vegetable bins Adjustable door shelves Door alarm Concealed hinge design	• • • • 2 3 2 6	• • • 2 3 2 6 •
Freezer Built in ice maker Ice bin and scoop Frost-free freezer Large plastic bin Small plastic bins Fast freeze Bottle Chill Ice cube trays Door alarm	• • • 2	• • 2 • •
Warranty		
Parts & labour Additional Sealed system parts	1 year 4 years	1 year 4 years

Product Dimenions	
Height	67 17/32"
Width	313/32"
Depth (excl. handle, incl. evaporator)	27 3/8"
Cabinetry Dimensions	
Inside height of cavity	68 5/16"
Flush with refrigerator chassis — full door rotation	
Inside width	3211/16"
Inside depth	24 13/32"
Inside width	37 1/32"
Inside width Inside depth flush to flat door	37 ⁷ / ₃₂ " 27 ³ / ₈ "
Inside depth flush to flat door	
Inside depth flush to flat door Flush with refrigerator door — 90° door rotation	27¾"
Inside depth flush to flat door Flush with refrigerator door — 90° door rotation Inside width Inside depth flush to flat door	27 3/8" 35 1/16"
Inside depth flush to flat door Flush with refrigerator door — 90° door rotation Inside width Inside depth flush to flat door	27 3/8" 35 1/16"
Inside depth flush to flat door Flush with refrigerator door — 90° door rotation Inside width Inside depth flush to flat door Minimum Clearances Side clearances	27 ³ / ₆ " 35 ¹ / ₆ " 27 ³ / ₆ "
Flush with refrigerator door — 90° door rotation Inside width Inside depth flush to flat door Minimum Clearances Side clearances Side clearance - hinge side flush with door - full rotation	27 ³ / ₈ " 35 ⁷ / ₆ " 27 ³ / ₈ "
Flush with refrigerator door — 90° door rotation Inside width Inside depth flush to flat door Minimum Clearances Side clearances	27 3/6" 35 7/16" 27 3/8" 25/52" 5 5/16"
Flush with refrigerator door — 90° door rotation Inside width Inside depth flush to flat door Minimum Clearances Side clearances Side clearance - hinge side flush with door - full rotation Side clearance - hinge side flush with door - 90° rotation	27 3/6" 35 7/6" 27 3/8" 25/32" 5 5/16" 3 17/32"
Inside depth flush to flat door Flush with refrigerator door — 90° door rotation Inside width Inside depth flush to flat door Minimum Clearances Side clearances Side clearance – hinge side flush with door – full rotation Side clearance – hinge side flush with door – 90° rotation Rear clearance (incl. evaporator tray)	27 %" 35 %6" 27 %1" 25/32" 5 %6" 31/32" 1 %6"














Counter	Depth	Bottom	Freezer

	Counter Depth Bottom Freezer		
Type of appliances	Ice & Water	Standard	
Models available	E522BRXU4 E522BLXU4	E522BRX4 E522BLX4 E522BRE4 E522BLE4	
Finish	EZKleen stainless steel curved door Curved handle	EZKleen stainless steel or white curved door Curved handle	
Dimensions (excl. handles)	H 671/8" W 313/32" D 285/32"	H 66 ¹⁵ / ₁₆ " W 31 ³ / ₃₂ " D 28 ⁵ / ₃₂ "	
Capacity Refrigerator Freezer Total	12.4 cu.ft. 5.2 cu.ft. 17.6 cu.ft.	12.4 cu.ft. 5.2 cu.ft. 17.6 cu.ft.	
Performance ActiveSmart™ Technology Frost free freezer Adaptive defrost Humidity control system Sabbath mode	•	•	
Refrigerator Ultra slim water dispenser lce boost SmartTouch™ Control Panel Silver prepainted cabinet LED lighting Bottle holders Adjustable Glass shelves Fruit & vegetable bins Adjustable door shelves Door alarm	• • • • • 2 3 2 6	• • • 2 3 2 6	
Freezer Built in ice maker Ice bin and scoop Frost-free freezer Large plastic bin Small plastic bins Fast freeze Bottle Chill Ice cube trays Door alarm	• • • • 2	• • 2 • •	
Warranty Parts & labour Additional Sealed system parts	1 year 4 years	1 year 4 years	

Pro	duct Dimensions	
A	Height - Ice & Water model/Standard model	671/8"/6615/16
B	Width	313/32"
©	Depth (excl. handle, incl. evaporator)	28 5/32"
Cal	oinetry Dimensions	
D	Inside height of cavity	68 5/16"
Flu	sh with refrigerator chassis — full door rotation	
E	Inside width	3211/16"
F	Inside depth	24 13/32"
Flu	sh with refrigerator door — full door rotation	
6	Inside width	37 1/32"
H	Inside depth flush to curved door	26 25/32"
Flu	sh with refrigerator door — 90° door rotation	
I	Inside width	35 1/16"
①	Inside depth flush to curved door	26 25/32"
Min	imum Clearances	
K	Side clearances	25/32"
L	Side clearance - hinge side flush with door - full rotation	5 5/16"
M	Side clearance - hinge side flush with door - 90° rotation	3 17/32"
N	Rear clearance (including evaporator tray)	13/16"
0	Vent (above refrigerator cabinet or around top of cupboard)	131/32"
P	Door clearance - hinge side flush with chassis - full rotation	2513/32"
@	Door clearance - hinge side flush with door - full rotation	20 1/8"










Counter	Depth	Bottom	Freezer
---------	-------	---------------	---------

	Counter Depth	Bottom Freezer	
Type of appliances	Ice & Water	Standard	
Models available	RF135BDRUX4 RF135BDLUX4	RF135BDRX4 RF135BDLX4	
Finish	EZKleen stainless steel flat door Designer handle Concealed hinge	EZKleen stainless steel flat door Designer handle Concealed hinge	
Dimensions (excl. handles)	H 67 ¹⁷ / ₃₂ " W 25" D 27 ³ / ₈ "	H 67 ¹ / ₃₂ " W 25" D 27 ³ %"	
Capacity Refrigerator Freezer Total	9.6 cu.ft. 3.9 cu.ft. 13.5 cu.ft.	9.6 cu.ft. 3.9 cu.ft. 13.5 cu.ft.	
Performance ActiveSmart™ Technology Frost free freezer Adaptive defrost Humidity control system Sabbath mode	•	•	
Refrigerator Ultra slim water dispenser Ice boost SmartTouch™ Control Panel Silver prepainted cabinet	•	•	
LED lighting Bottle holders Adjustable Glass shelves Fruit & vegetable bins Adjustable door shelves Door alarm	• 2 2 2 6 • •	• 2 2 2 6 • •	
Concealed hinge design Freezer Built in ice maker Ice bin and scoop Frost-free freezer Large plastic bin Small plastic bins Fast freeze	•	• • 2	
Bottle Chill Ice cube trays Door alarm	•	•	
Warranty Parts & labour Additional Sealed system	1 year 4 years	1 year 4 years	

parts

Product Dimensions					
A	Height	67 17/32"			
B	Width	25"			
©	Depth (excl. handle, incl. evaporator)	27 3/8"			
Cal	pinetry Dimensions				
D	Inside height of cavity - Standard / Ice & Water model	68 5/16"			
Flu	sh with refrigerator chassis — full door rotation				
E	Inside width of cavity	26 % 6"			
F	Inside depth of cavity	24 13/32"			
Flu	sh with refrigerator door — full door rotation				
6	Inside width of cavity	313/32"			
H	Inside depth of cavity flush to flat door	27 3/8"			
Flu	sh with refrigerator door — 90° door rotation				
I	Inside width of cavity	29 11/32"			
(J)	Inside depth of cavity flush to flat door	27 3/8"			
Min	imum Clearances				
K	Side clearances	25/32"			
L	Side clearance - hinge side flush with door - full rotation	5 1/16"			
M	Side clearance - hinge side flush with door - 90° rotation	3 17/32"			
N	Rear clearance (including evaporator tray)	13/16"			
0	Vent (above refrigerator cabinet or around top of cupboard)	1 31/32"			
P	Rear clearance (including evaporator tray)	20 15/32"			
(a)	Vent (above refrigerator cabinet, around top of cupboard)	15 15/16"			





Your refrigerator door is the most used door in your home and every time it is opened the temperature changes around your food. The challenge is maintaining a consistent and controlled environment despite ongoing changes inside and outside the refrigerator. ActiveSmart™ Technology achieves this through constantly monitoring how you and your family use your refrigerator, adjusting airflow to maintain a stable and even temperature. So despite highs, lows and occasional gusty winds, when it comes to your refrigerator, let ActiveSmart™ control the weather to deliver better food care.



A PEACE OF MIND SALE

Fisher & Paykel has a 24/7 customer care enquiry service that allows you to speak to a real person - whether it be regarding which appliance would suit your particular needs, to arranging a qualified technician to install or service your product

T 888.936.7872 **E** customercare@fisherpaykel.com