

# LED

## Versa Bar

### Extra Long Run

### Cool White

### Dimmable



Clips Included

VERSAS BAR XLR  
CLEAR LENS



“Connect even more Versa Bars together without voltage drop” 

• QUICK MOUNT MAGNETS MOUNTED INTO THE BACK OF BAR

CLEAR MODELS  VSCXLR10CW24V  VSCXLR20CW24V  VSCXLR30CW24V  VSCXLR40CW24V  VSCXLR70CW24V

FROSTED MODELS  VSFXLR10CW24V  VSFXLR20CW24V  VSFXLR30CW24V  VSFXLR40CW24V  VSFXLR70CW24V

COLOR; cool white	6250K	6250K	6250K	6250K	6250K
XLR LENGTH	10.39"	20.24"	30.08"	39.92"	69.48"
LUMEN OUTPUT (clear)	203	405	608	810	1418
LUMEN OUTPUT (frosted)	175	349	523	698	1221
WATTAGE	3W	6W	9W	12W	21W
CURRENT	0.13 amps 24V DC	0.25 amps 24V DC	0.38 amps 24V DC	0.5 amps 24V DC	0.88 amps 24V DC
MAX RUN/driver	32 feet	32 feet	32 feet	32 feet	32 feet
VOLTAGE	<b>24V DC ONLY</b>	<b>24V DC ONLY</b>	<b>24V DC ONLY</b>	<b>24V DC ONLY</b>	<b>24V DC ONLY</b>
WIDTH • HEIGHT (XLR)	0.94"W x 0.55"H	0.94"W x 0.55"H	0.94"W x 0.55"H	0.94"W x 0.55"H	0.94"W x 0.55"H
VIEWING ANGLE	90°	90°	90°	90°	90°
WARRANTY (YEARS)	5	5	5	5	5

CONNECTORS available for all configurations (pg 68)

POWER SUPPLIES 6 to 300 watt (pg 69 - 72)

CUSTOMIZING custom sizing available between 10" and 70" consult LED Lighting Inc.

NOTE • lumen output +/- 10%

#### FEATURES

- aluminium alloy housing
- 6" lead length on either end.
- easy mounting clip & screw installation includes flat (180°) clips, angled (45°) clips available separately (pg 68)
- mounts to wood, steel or metal & most hard smooth surfaces
- damp location
- solid-state, high shock and vibration resistant
- no UV or IR radiation
- occupancy and infrared sensor available (pg 57)

#### OPTIONS

- All Versa Bars are available with a connector on one end and dead end (no connector) on the other end, please consult factory for options and pricing.
- All Versa Bars are available with waterproof connectors, please consult factory for options and pricing.