

LED

Versa Bar

Extra Long Run

Neutral White

Dimmable



“Connect even more Versa Bars together without voltage drop” 

• QUICK MOUNT MAGNETS MOUNTED INTO THE BACK OF BAR

CLEAR MODELS VSCXLR10NW24V VSCXLR20NW24V VSCXLR30NW24V VSCXLR40NW24V VSCXLR70NW24V

FROSTED MODELS VSFXLR10NW24V VSFXLR20NW24V VSFXLR30NW24V VSFXLR40NW24V VSFXLR70NW24V

COLOR; neutral white	4300K	4300K	4300K	4300K	4300K
XLR LENGTH	10.39"	20.24"	30.08"	39.92"	69.48"
LUMEN OUTPUT (clear)	185	365	545	725	1265
LUMEN OUTPUT (frosted)	159	314	469	624	1089
WATTAGE	3W	6W	9W	12W	21W
CURRENT	0.13 amps 24V DC	0.25 amps 24V DC	0.38 amps 24V DC	0.5 amps 24V DC	0.88 amps 24V DC
MAX RUN/driver	32 feet	32 feet	32 feet	32 feet	32 feet
VOLTAGE	24V DC ONLY	24V DC ONLY	24V DC ONLY	24V DC ONLY	24V DC ONLY
WIDTH • HEIGHT (XLR)	0.94"W x 0.55"H	0.94"W x 0.55"H	0.94"W x 0.55"H	0.94"W x 0.55"H	0.94"W x 0.55"H
VIEWING ANGLE	90°	90°	90°	90°	90°
WARRANTY (YEARS)	5	5	5	5	5

CONNECTORS available for all configurations (pg 68)

POWER SUPPLIES 6 to 300 watt (pg 69 - 72)

CUSTOMIZING custom sizing available between 10" and 70" consult LED Lighting Inc.

NOTE

- lumen output +/- 10%

FEATURES

- aluminium alloy housing
- 6" lead length on either end.
- easy mounting clip & screw installation includes flat (180°) clips, angled (45°) clips available separately (pg 68)
- mounts to wood, steel or metal & most hard smooth surfaces
- damp location
- solid-state, high shock and vibration resistant
- no UV or IR radiation
- occupancy and infrared sensor available (pg 57)

OPTIONS

- All Versa Bars are available with a connector on one end and dead end (no connector) on the other end, please consult factory for options and pricing.
- All Versa Bars are available with waterproof connectors, please consult factory for options and pricing.