

GAS & PROPANE BATTERY CHARGING DC GENERATORS





ALTEN is a recognized Honda and Subaru D-OEM manufacturer of gas and propane battery-charging DC generators.

Originally developed and produced in Australia since 1998, ALTEN assembles the entire product line in the USA for the North American market. Rugged and reliable, ALTEN Battery-Charging DC Generators are ready to boost or recharge batteries anywhere, anytime.

Large or small battery systems can be recharged quickly and safely during emergencies, repairs or scheduled maintenance. Any 12 or 24 volt battery used with renewable energy systems, heavy industrial equipment, commercial marine or telecom applications can be quickly recharged with an ALTEN Battery-Charging DC Generator. Check out our Duke lineup of diesel DC generators and custom design-build packages for specific remote power applications.

ALTEN

MODEL NUMBER	G1	G2	G3	P1	
Models					
Voltage Model	12 Volt	12 / 24 Volt	12 / 24 Volt	12 / 24 Volt	
Low Voltage (Float)	14.0 V Regulated	14.0 / 28.0 V Regulated	14.0 / 28.0 V Regulated	-	
High Voltage (Bulk)	14.8 V Regulated	14.8 / 28.8 V Regulated	14.8 V / 28.8 V Regulated	14.8 V / 28.8 V Regulated	
Max Amp Output	55 Amps	120 / 45 Amps	160 / 80 Amps	120 / 45 Amps	
Voltage Cut Out	18 Volts	18 / 36 Volts	18 / 36 Volts	18 / 36 Volts	
Weight	12kg / 26lbs	26kg / 57lbs	31kg / 68lbs	56kg / 123lbs	
Dimensions (LxWxH)	16.1" / 10.8" / 14.6"	20.0" / 15.2" / 15.0"	20.0" / 15.2" / 15.0"	20.0" / 20.0" / 20.0"	
Engine	Honda GXH50	Honda GX160	Honda GX200	Subaru Air-cooled	
Max Engine Power *	2.1HP, 7000rpm	4.8HP 3600rpm	5.5HP 3600rpm	5.7HP @ 4000 RPM	
Fuel Capacity	.77L / .2 US Gal	3.1L / .82 US Gal	3.1L / .82 US Gal	3/8" fuel connection	
Fuel Consumption	~ 4 Hour Run Time	~ 4 Hour Run Time	~ 4 Hour Run Time	0.4 m3/hr @ 100% load	
Fuel Type	Gasoline	Gasoline	Gasoline	Propane (ALTEN converted)	
Oil Capacity	.25L / .26 Qt	.6L / .63 Qt	.6L / .63 Qt	.6L/.63Qt	
Start Type	Recoil	Recoil / Electric	Recoil / Electric	12v Electric Start & Recoil Pull Start Automatic Start & Remote Start (2 wire)	
Noise Level (max)	74 dBa @ 7M	74 dBa @ 7M	74 dBa @ 7M	74dBa @ 7M	
Engine Warranty	Honda 3-Year	Honda 3-Year	Honda 3-Year	Subaru 5-Year	
Product specifications and model availability are subject to change without notice.					

* The power rating of the engine indicated is the net power output tested on a production engine for the engine model and measured in accordance with SAEJ1349 at 3600 RPM. Mass production engines may vary from this value. Actual power ouput for the engine installed in the final machine will vary depending on numerous factors, including the operating speed of the engine in application, environmental conditions, maintenance, and other variables. - Honda USA

	1-888-ON-ALTEN (662-5836)	Authorized Reseller:
	www.altendc.com	
٥	Manufactured in USA	