



PYRODOX™ GP 500 MICA CABLE TAPE

We'll help you meet the challenge of finding unique solutions to your most critical problems

PROPERTIES (TYPE P)

Thickness (mm)	.125 +/- 0.02
Weight (g/m ²)	172 +/- 12
Mica Content (g/m ²)	120 +/-5
Binder Type	Halogen free High Temperature Silicone
Binder Content (g/m ²)	20 +/-3
Glass Content (g/m ²)	32 +/-3
Tensile Strength (N/cm)	> 120
Dielectric Strength	>1.2KV
Shelf Life @ 20°C	12 months

Tests to determine application suitability should be made by each user. Electrolock can not guarantee performance in the user's application. Copyright 2015 Electrolock, Incorporated.



www.wirecableinsulation.com

> Description

Pyrodox GP 500 is a special heat treated phlogopite mica cable tape with a silicone binder and fiberglass backing. The tape is engineered to withstand extreme electrical and thermal overloads as well as high moisture environments which permit its use in cables having extended fire survival time. Pyrodox GP 500 is used in applications which include fire survival for control and power cables, mass transit, aircraft, oil well, thermocouple, appliance wire and shipboard cables.

> Availability

The tape is provided in slit pads or traverse packs in lengths that can vary at the customers request.

> For more information

For more information on this product or any other fine Electrolock products, please contact your nearest sales Representative at (440) 834-7500



17930 Great Lakes Parkway Hiram, OH 44234 Phone 440.834.7500 Fax 440.834.7525 1-19-15