

FASTER

250 mm PER SECOND (PRINT) 400 mm PER SECOND (TRAVEL)



PRECISION

IMPROVED RESOLUTION HIGH DEFINITION"



HEATED BED

PRECISION CERAMIC BUILD SURFACE USE WITH WOLFBITE ADHESIVES - NO BUILD TAPE NEEDED



PRINT BIGGER

FULL-SIZE PROTOTYPES, MOLDS AND PRODUCTION RUNS



RUGGED DESIGN

POLYCARBONATE / ALUMINUM FRAME



EASY TO USE

AUTO LEVELING CLOUD BASED SLICING



FEATURES

- Independently Controllable Hotends
- Create Soluble Support Structures to Eliminate Post Processing
- Powerful Quad-Fan Material Cooling System
- Interchangeable Nozzles (from 0.35 to 0.50 mm)
- Combine 2 Materials or 2 Colors in One Print
- Feature Large 12 x 8 x 9.5" Build Volume
- Provided Print Settings Allow for Easy Dual Color or Dual Material Setup



FEATURES

- Print in Over 40+ Materials from TPU to Polycarbonate
 - Wi-Fi, Ethernet, USB and Micro SD
 - High Temperature Dual Printheads 315 °C ◀
 - Core XY Motion System <
 - Enclosed Chamber <
 - Auto-Leveling <
 - Minimum Layer Height of 40 Microns (100 or Above Recomended)









