

Datasheet 89-OFM-PMC-121-001



Standard Configuration

- Industrial-Grade LCD
- Multi-Touch Capacitive Sensor (G/G)
- · Optically Bonded
- HDMI/DVI/VGA Input
- Powder Coated Steel Housing
- Rear VESA Mounts
- Adjustable Flange Side-Mounts
- USB Plug-And-Play Windows 7+
- Cables Included

Customizable Features

- Sunlight Readable / Superbright / NVIS
- SBC / Media Integration
- Custom Cover Glass and Graphics
- Fresh and Salt Water Resistant Touch
- Gloved Touch
- Ruggedization

APPLICATIONS

- Aerospace
- Medical
- Military
- Industrial
- Transportation
- Retail & Public Use

12.1 Open Frame Monitor

The new OFM Series Open Frame Touch Monitors provide a drop-in, completely integrated, industrial solution. Standard configurations come ready to plug-and-play right out of the box. Multiple video inputs and USB-powered touch screen allow for easy implementation in your enclosure. To further maximize ease of integration we have two VESA mounting options on the rear and adjustable side mounting flanges. The black powder coated steel enclosure provides the fit and finish of a custom product with the strength and durability to protect your investment for years of worry free operation.

Specifications

12.1"
0.204 mm x 0.204 mm
1280 x 800
178° H / 178° V
500 nits
16.7 million
25 ms
1000:1
16:10
Projected Capacitive Multi-touch
5 ms
HDMI, VGA, DVI
-30° to 85° C
Open Frame
4 Side Mount Holes
Powder-coated Steel
6.05 lbs
1 yr Parts & Labor











