



**product introduction**

The LM Series are the smallest linear lights available with an integrated built in driver. The driver features the new Multi-Drive™ which allows the user to operate this light in either constant ON operation or OverDrive depending on wiring method. The industry standard 5 Pin M12 connector makes for simple wiring and the multiple lensing options gives this light a broad range of illumination area. The 0-10V analog control gives the user total control over intensity.


**product features**


- Driver Built In – No External Wiring To A Driver
- 5 Pin M12 Quick Disconnect Cable
- Over-Current Protection
- PNP and NPN ON/OFF Input
- Continuous Operation or OverDrive Mode
- (4) High Output LEDs


**constant ON product specs**
**Wiring configuration for CONSTANT ON operation**

	Pin	Function	Signal	Wire Color
	1	Power In	+24VDC	<b>BROWN</b>
	2	NPN	Ground (common)	<b>WHITE</b>
	3	GND	Ground	<b>BLUE</b>
	4	PNP	> 4VDC	<b>BLACK</b>
	5	Intensity Control	1-10VDC	<b>GREY</b>


\* Some cables use green with yellow stripe for 1-10V adjustment.

\* Either a negative NPN or a positive PNP signal, not both must be applied for light to function.

<b>Electrical Input</b>	24 VDC +/- 5%
<b>Current</b>	.10 - .12A <i>NOTE: current is LED color dependent</i>
<b>Wattage</b>	28.8W
<b>Strobe Input</b>	PNP ► +4VDC or greater to activate   NPN ► GND (<1VDC) to activate
<b>PNP Line</b>	4mA @ 5VDC   8mA @ 10VDC   15mA @ 24 VDC
<b>NPN Line</b>	10mA @ Common (0VDC)
<b>Continuous Mode</b>	Light will be in continuous mode by leaving signal on strobe input active – <i>analog dimming is active</i>
<b>Connection</b>	5 pin M12 connector
<b>Lifespan</b>	100,000 hrs
<b>IP Rating</b>	IP65
<b>Certification</b>	CE and RoHS certified
<b>Weight</b>	52g
<b>Ambient Temperature</b>	-40° - 50° C (-40° - 122° F)



Wiring configuration for OverDrive operation

	Pin	Function	Signal	Wire Color
	1	Power In	+24VDC	BROWN
	2	NPN	Sinking Signal	WHITE
	3	GND	Ground	BLUE
	4	PNP	Sourcing Signal	BLACK
	5	OverDrive Signal	Ground	GREY

- \* Some cables use green with yellow stripe for 1-10V adjustment.
- \* A strobing negative NPN or a positive PNP signal, not both must be applied for light to function.
- \* No analog to OverDrive operation.

Electrical Input	24 VDC +/- 5%
Current	.85 - .97A NOTE: current is LED color dependent
Wattage	23.3W
Strobe Input	PNP ► +4VDC or greater to activate   NPN ► GND (<1VDC) to activate   5µS LED activation time
PNP Line	4mA @ 5VDC   8mA @ 10VDC   15mA @ 24 VDC
NPN Line	10mA @ Common (0VDC)
OverDrive Mode	Connect Pin 5 to GND (more info. in wiring configuration) – analog dimming is inactive
Duty Cycle	Max.10%
Strobe Duration	Max. 125mS



product number key

LM45 – XXX – X

—» Part Number Key


<b>Product Family:</b> Mini Linear LM45 Series	<b>Color:</b> 470 - Blue 530 - Green 625 - Red 850 - IR WHI - White	<b>Lens:</b> W – 80° wide
--	--	------------------------------

- \* Standard 40 degree lens included
- \* Wide lens options available

CE and RoHS Compliant




warnings

	<b>Attention</b> Please note that the power requirements are 175mA at 24VDC for constant ON and 800mA for OverDrive. Failure to supply light with appropriate current will result in non-repeatable lighting. Contact Smart Vision Lights for more information.
---	--




## mounting & accessories



Housing includes T-slot for easy mounting

Hardware includes:

- (2) M4x16 screws
- (2) M4 nylon nuts



## optical performance

### LM45-XXX (40° lens)

Working Distance mm (inches)	Pattern (80%-100% measured intensity) mm (Inches)		
0.25m (9.84")	120mm(~4.7") H x 125mm(~4.9") V		
0.5m (19.7")	260mm(~10.2") H x 260mm(~10.2") V		
Typical output performance		Constant ON Illumination (lux)	OverDrive Illumination (lux)
Distance = 0.25 meter		3,600	18,000
<i>Illumination measurement taken on White Lights – 6500K</i>			

### LM45-XXX-W (80° lens)

Working Distance mm (inches)	Pattern (80%-100% measured intensity) mm (Inches)		
0.25m (9.84")	240mm(~9.4") H x 250mm(~9.8") V		
.5m (19.7")	520mm(~20.4") H x 520mm(~20.4") V		
Typical output performance		Constant ON Illumination (Lux)	OverDrive Illumination (Lux)
Distance = 0.25 meter		1,200	6,000
<i>Illumination measurement taken on White Lights – 6500K</i>			