

NSR-9854XL

Tactical Dual-Light[™] Flashlight USB Rechargeable

MARKET APPLICATIONS	Law enforcement, fire & rescue, industrial, security, hardware/tool, automotive, hunting/recreation.
DESCRIPTION	The NSR-9854XL USB Rechargeable Xtreme Lumens [™] Multi-Function Tactical Dual-Light [™] Flashlight uses a CREE [®] LED rated at 850 lumens working in conjunction with a high-efficiency deep parabolic reflector to create a usable beam of light rated at 280 meters. A 200 lumen unfocused floodlight is integrated in to the housing which is perfect for close-up illumination. Both the flashlight and the floodlight can be turned on at the same time for maximum safety and versatility. The NSR-9854XL has a unique tail-switch that operates both the flashlight and floodlight in one configuration. The upper portion of the switch operates the flashlight that provides both momentary or constant-on functionality with high, medium or low-brightness settings as well as a disorienting strobe and the lower portion of the switch operates a downward facing floodlight. The housing, tail-cap and bezel are made from aircraft-grade 6061-T6 aluminum with a Type III hard-anodized finish. Power comes from a rechargeable Lithium-ion battery.
CASE MATERIAL	Aircraft-grade 6061-T6 Aluminum with Type III Hard Anodized Finish - Black
DIMENSIONS	Length: 6.7 inches (177 mm) • Handle diameter: 1.1 inches (27 mm) • Head diameter: 1.5 inches (38 mm)
WEIGHT	Weight: 8 oz. (227g) with battery installed.
LENS	Unbreakable polycarbonate with scratch resistant coating.
LIGHT SOURCE	Cree® LED. Impervious to shock with a 50,000 hour lifetime.
LIGHT OUTPUT	Flashlight: High - 850 lumens, Medium - 550 lumens, Low - 180 lumens, • Floodlight: 200 lumens • Dual-Light: 300 lumens
ON/OFF	Upper Tail Switch - Momentary or Constant-on Flashlight, High, Medium and Low-Brightness Flashlight, Strobe Lower Tail Switch - Floodlight & Dual-Light
RUN-TIME	Flashlight: High - 2 hours, Medium - 2.5 hours, Low - 9 hours • Floodlight: 2.5 hours • Dual-Light: 2.5 hours
BATTERY	Lithium-ion battery
CHARGING	Charges in 4 hours (typical) on 100 / 240 50/60 Hz or 12V DC.
FEATURES	 Super-bright Xtreme Lumens[™] design CREE[®] LED technology – 50,000 + hours LED life Flashlight/Floodlight/Dual-Light[™] Momentary or constant-on flashlight, 3 brightness levels & strobe Sharp focused beam for distance illumination Unfocused wide-beam floodlight for close-up illumination Aircraft-grade 6061-T6 aluminum housing, tail-cap and bezel Type III hard anodized finish with non-slip grip Dual-function tail-switch Waterproof Impact & chemical resistant Meets the requirements of NFPA-1971-8.6 (2013) Serialized for personal identification Powered by rechargeable Lithium-ion battery (included) Can also be powered by two CR-123 Batteries (not included) using the CR-123 Battery Carrier (included) Limited Lifetime Warranty • Includes the LEDs, housing and lenses. Rechargeable batteries, chargers, switches,
WARRANTY	electronics and included accessories are warranted for a period of two years with proof of purchase. Disposable, non- rechargeable batteries are excluded from this warranty. Normal wear and failures which are caused by accidents, misuse, abuse, faulty installation and lightning damage are also excluded.
APPROVALS	Image: Constraint of the state of the s

Designed in USA, manufactured in China at a ISO-9001 certified Bayco facility.

PDS_NSR-9854XL_16

1

0 HOURS