



Getac Z710 Rugged Android Tablet

PRODUCT SPECIFICATIONS

DURABILITY

- Fully Rugged
- MIL-STD-810G and IP65 Certified
- Vibration Resistant
- Drop Resistant (26 Drops from 1.82m / 6ft)
- Optional ANSI/ISA 12.12.01
- Optional ATEX certified

PROCESSOR

- OMAP 4430 Dual Core 1Ghz

OPERATING SYSTEM

- Android 4.1

STORAGE & MEMORY

- 1GB MDDR
- 16GB NAND Flash

DISPLAY

- 7.0" TFT LCD WSVGA (1024 x 600)
- LumiBond® Sunlight Readable Display with Glove-On Capacitive Touchscreen

EXPANSION SLOT

- Micro SDHC (Up to 32GB)

CAMERA

- HD Web Camera
- 5MP Pixel Auto Focus Camera

INTEGRATED COMMUNICATIONS

- 802.11 b/g/n
- Bluetooth (v2.1+EDR class 2)
- SiRFstarIVTM GPS (With Internal Antenna)
- Optional 3.5G WWAN (voice and data) (HSPA+/UMTS/EDGE/GPRS/GSM)

I/O INTERFACES

- USB (Client 2.0) x 1
- USB (Host 2.0) x 1
- Microphone x 1
- Speaker x 1
- DC in Jack x 1
- Docking connector (30-pin) x 1
- RF antenna pass-through for GPS and WWAN

GPS SENSOR

- Chipset: SiRFstarIVTM
- Receiver Type: L1 (C / A)
- Channels: 48 Channels All-in-View Tracking Update Rate: 1Hz
- Horizontal Accuracy:
 - i) Autonomous: 2.5m / 8.2ft
 - ii) DGPS: 2.0m / 6.56ft
- Average Cold Start Time: 35s
- Average Warm Start Time: 35s
- Average Hot Start Time: 1s
- Average Reacquisition: 0.1s

SPECIAL FEATURES

- E-Compass
- Optional 1D/2D Imager Barcode Reader
- Optional 13.56MHz RFID and Contactless Smart Card Reader (ISO 15693 and 14443 A/B Compliant)

POWER

- AC Adapter (24W; 12V/2A, 100-240VAC; 50 / 60 Hz)
- Lithium-Polymer Smart Battery (7600 mAh) (Up to 10 Hours of Battery Life)
- Charging Time: Sleep Mode, Approx. 6 Hrs

TEMPERATURE

- Operating Temp: -4 °F to 122 °F / -20 °C to 50 °C
- Storage Temp -40 °F to 158 °F / -40 °C to 70 °C
- Humidity: 95% RH, non-condensing

SECURITY


- WiFi for WPA / WPA2 Operation Authentication: OPEN, SHARED-Key, PEAP (MS-CHAPv2, TLS, GTC, OTP, MD5-Challenge), EAP (SIM, AKA, PSK, PAX, SAKE, GSK), TLS, EAP-TTLS (PAP, CHAP, MS-CHAP, MS-CHAPv2, EAP-TLS, EAP-MSCHAPv2, EAP-OTP, EAP-GTC, EAP-MD5-Challenge)
- Encryption: WEP, AES, TKIP

DIMENSIONS/WEIGHT

- 8.58" x 5.6" x 1.08" (21.8 x 14.2 x 2.7cm)
- 1.77lb / 800g

WARRANTY

- Three-year bumper-to-bumper warranty standard



Group Mobile
5590 W. Chandler Blvd. Suite 3
Chandler, AZ 85226
Toll Free: 1-866-RUGGED8
GroupMobile.com