



Getac A140 Rugged Tablet

PRODUCT SPECIFICATIONS

DURABILITY

- MIL-STD 810G and IP65 certified
- MIL-STD 461F ready2
- Optional ANSI/ISA 12.12.01
- Vibration & drop resistant

PROCESSOR

- Intel® Core i5-6200U 2.3GHz processor with Turbo Boost Technology up to 2.8GHz 3MB Intel Smart Cache
- Intel® Core i5-6300U vPro™ 2.4GHz processor with Turbo Boost Technology up to 3.0GHz 3MB Intel Smart Cache
- Intel® Core i7-6500U 2.5GHz processor with Turbo Boost Technology up to 3.1GHz 4MB Intel Smart Cache
- Intel® Core™ i7-6600U vPro™ 2.6GHz processor with Turbo Boost Technology up to 3.4GHz 3MB Intel Smart Cache

OPERATING SYSTEM

- Windows 10 Professional
- Windows 7 Professional (Optional downgrade)

STORAGE & MEMORY

- OPAL 2.0 Solid State 128GB
- Optional OPAL 2.0 256GB nor 512GB solid state drives

DISPLAY

- 14" TFT LCD (1366x768) 1000 NITs LumiBond™ 2.0 sunlight readable LED display with multi-touch technology (hard-tip stylus)
- Optional 14" IPS TFT LCD FHD (1920 x 1080) 800 NITs LumiBond™ 2.0 sunlight readable LED display with multi-touch technology (hard-tip stylus)

VGA CONTROLLER

- Intel HD Graphics 520

EXPANSION SLOT

- Optional 1D/2D imager / barcode reader
- Optional serial port or VGA
- Optional fingerprint scanner
- Optional RFID

INTEGRATED COMMUNICATIONS

- 10/100/1000 base-T Ethernet x 2
- Intel Dual Band Wireless-AC 8260 (802.11ac)
- Bluetooth (v4.2)
- Optional dedicated GPS
- Optional 4G LTE multi-carrier mobile broadband

I/O INTERFACES

- DC in x 1
- Ethernet x 2
- MicroSD USB 3.0 (9-pin) x 2
- USB 2.0 (4-pin) x 1
- Docking port (24-pjn) x 1
- Headphone out/Mic-in Combo x 1
- HDMI x 1
- Optional RF antenna pass-through for GPS, WLAN and WWAN

WEBCAM

- Optional FHD webcam x 1
- Optional 8MP auto-focus camera

KEYBOARD & INPUT

- Eight tablet buttons: Windows, Power, Camera Capture, Barcode Reader Trigger, OSDC, Rotation Lock, Volume Up, Volume Down

POWER

- AC Adapter (65W, 100-240VAC, 50/60Hz)
- Hot swappable Dual Li-Ion battery (3220mAh) x 2

TEMPERATURE

- Operating Temp: -5.8 °F to 140 °F / -21 °C to 60 °C
- Storage Temp: -60 °F to 160 °F / -51 °C to 71 °C
- Humidity: 95% RH, non-condensing

SECURITY

- Intel vPro Technology (per CPU options)
- TPM 2.0
- Cable lock slot
- NIST BIOS compliant
- Smartcard reader
- Optional fingerprint reader
- Optional contactless smart card reader
- Optional Absolute™ DDS software
- TPM 1.2
- Cable lock slot
- NIST BIOS compliant
- Optional 13.56MHz RFID
- Optional contactless smart card reader

DIMENSIONS/WEIGHT

- 14.53" x 9.76" x 1.28" (369 x 248 x 32.5mm)
- 5.07lbs (2.3kg)

WARRANTY

- Three-year bumper-to-bumper warranty standard



Group Mobile
5590 W. Chandler Blvd. Suite 3
Chandler, AZ 85226
Toll Free: 1-866-RUGGED8
GroupMobile.com