

Press Release Quick Tips

New 90 Series - LED panel mount indicator offer superior construction and longer life.

Cartridge, Bi-Pin and Wire Leads Termination Styles

Distribution Date: May 7, 2018

Product Name: 90 Series

Product Description: 0.290" (7.37mm) LED Panel Mount Indicator

Key Markets/Applications:

Industrial equipment

Transportation

Signal indicator

Maintenance and warning display

TrucksAircraft

Status indication

Instrumentation

Key Benefits

- Cartridge, bi-pin and wire leads termination styles for use with spring retainer clip, socket holder or wiring plugs
- Available with a variety of LEDs including AllnGaP and InGaN technology for high brightness applications, bi-color and with integrated resistors
- Available in six single colors: red, green, white, blue, amber, orange and in one bi/color: red/green with or without lens
- Offered with a variety of lens options: cylindrical, flush, dome, wide cylindrical or wide flush all featured with fresnel pattern lens which provide excellent light focus and assure maximum light output
- Spring retainer clip and washer (included) secures uniform placement of the indicator to the panel and is ideal for high vibration environments
- Watertight socket options for splashdown environments
- For use with spring retainer clip (included), socket holder (PS90 or PS90T - sold separately) or wiring plug (SH90 or CSH90 - sold separately)
- Designed for quick installation in display panels and reduces overall cost due to less-frequent replacements

Product Specifications

- · Prominent LED panel mount indicator
- Panel hole diameter: 0.290" (7.37mm)
- Built-in LED can be used with DC circuits (2 to 60 VDC) or 120VAC circuits
- · Terminal Styles: Cartridge, Bi-Pin and Wire Leads
- (6" 24 AWG wire leads)
- Offered with a variety of LEDs
- Single color: red, green, white, blue, amber and orange
- · Bi-color: red/green
- Available with no lens, cylindrical lens, flush lens or dome lens
- · Black bezel offering to enhance LED contrast
- Resistant to shock and vibration
- Mounting hardware provided (spring retainer clip and washer)
- For use with socket holder (PS90 or PS90T sold separately) or wiring plug (SH90 or CSH90 - sold separately)
- Watertight socket options for splashdown environments
- Compliant with RoHS and REACH requirements

For additional information about VCC, please visit vcclite.com