



DESCRIPTION

The **CBS ArcSafe® RRS-3 Selpact** single-application remote racking system (RRS-3) is designed to operate the Merlin Gerin Selpact air circuit breaker without the need for any modifications to existing electrical equipment, thanks to CBS ArcSafe's magnetic latching system. The lightweight, portable RRS-3 Selpact allows technicians to remotely install and remove a breaker while standing up to 300 feet away. The RRS-3 Selpact is compatible with Merlin Gerin Selpact air circuit breakers with ratings of 1600 A, 2000 A, 2500 A, and 3200 A, including the DN2, DN2-H, DS2, DS2-H, DR2, and DRS2. Typical applications include protection and switching of three-phase, four-wire power systems up to 660 V AC. Designed, manufactured, and assembled in the United States, all RRS-3 units are portable, with fast and easy setup. They offer mechanical and/or electrical safety protections, adjust to fit unique electrical equipment configurations, reduce requirements for personal protection equipment, and help customers with NFPA 70E arc-flash safety compliance. Optional features include 25-foot extension cables, a 24 V DC LED light, a wireless video camera system with an LCD monitor, and a rugged protective case assembly.



SPECIFICATIONS

WEIGHT:	22 lbs
DIMENSIONS:	8.2" H x 21" W x 13.8" D
POWER CONSUMPTION:	100 W
OPERATING DISTANCE:	25–300 feet
COMPATIBILITY:	Merlin Gerin Selpact air circuit breakers 1600/2000/2500/3200 A (including DN2, DN2-H, DS2, DS2-H, DR2, and DRS2)
CONTROL/POWER SOURCE:	CBS ArcSafe® RSO-IV control console

OVERVIEW

- Remote operation from up to 300 feet away
- Lightweight and portable for hard-to-access areas
- Simple setup; no equipment modification required
- Reduces or eliminates need for arc-flash hazard suits
- Designed, manufactured, and assembled in the USA

