

## Press Release Quick Tips

New T-2 slide based LED lamps delivers reliable, long life and preferable indication

Distribution Date: October, 2018 Product Name: T-2 Slide Based LED Lamp Product Description: T-2 Slide Based Replacement LED Lamp Key Markets/Applications:

- Industrial Equipment
- Power Systems
- Switch Gear Equipment
- Signal Indicator

- Utility Displays
- Power Plants

Key Benefits	Product Specifications
<ul> <li>LED replacement for incandescent lamps in a variety of colors and voltages</li> <li>T-2 Slide based LED replacement lamps delivers reliable, long life and preferable indication</li> <li>LED replacement bulb is perfect for industrial indicator lights and functions as an LED pilot light bulb</li> <li>Offered with ANSI No.2, ANSI No. 5, T5.5 telephone slide bases</li> <li>Available with a variety of LEDs and provides low energy consumption, fast on/off cycling, low heat generation, and long operating life</li> <li>Available in six single colors: red, amber, green, orange, blue, white and one bi-color red/green combination</li> <li>Low power consumption - uses up to 90% less energy than an incandescent lamp</li> <li>LEDs operate significantly cooler than traditional lamps</li> <li>Designed for quick installation and reduces overall cost due to less-frequent replacements</li> </ul>	<ul> <li>T-2 Slide based LED lamp (light bulb)</li> <li>Voltage: 2-60 VDC or 120VAC</li> <li>ANSI No.2, ANSI No. 5, T5.5 Telephone Slide Bases</li> <li>Available in six LED single colors: red, amber, green, orange, blue, white</li> <li>Available in one bi-color: red/green</li> <li>Low power consumption - uses up to 90% less energy than an incandescent lamp</li> <li>Single chip based LED</li> <li>Available with built-in diffuser for wide angle viewing</li> <li>Mounts directly into industry standard socket</li> <li>Operation temperature: -30C to +60C</li> <li>Storage temperature: -40C to +100C</li> <li>Low heat generation, LEDs operate significantly cooler than traditional lamps</li> <li>Designed for quick installation and reduces overall cost due to less-frequent replacements</li> <li>Reliable, fast on/off cycling, shock resistance and long operating life</li> <li>Compliant with RoHS and REACH</li> </ul>

## For additional information about VCC, please visit vcclite.com

