

## RSA-224

### Eaton/Cutler-Hammer Busway Plug 100–200 A



### DESCRIPTION

The **CBS ArcSafe® RSA-224** remote switch actuator (RSA) is designed to operate the Eaton/Cutler-Hammer busway plug with no modification to existing electrical equipment, thanks to CBS ArcSafe's magnetic latching system. The lightweight, portable RSA-224 allows technicians to remotely close or trip the Eaton/Cutler-Hammer busway plug from a safe distance of up to 300 feet while stationed outside the arc-flash boundary. The RSA-224 is compatible with Eaton/Cutler-Hammer POW-R-WAY lineup of 100–200 A busway systems. Typical applications include protection and control of low-voltage power distribution systems up to 240 V AC. Designed, manufactured, and assembled in the United States, all RSA units are portable, with fast and easy setup. They offer mechanical and/or electrical safety protection, adjust to fit unique electrical equipment configurations, reduce requirements for personal protection equipment, and help customers with NFPA 70E arc-flash safety compliance. Optional features include a radio remote with range up to 300 feet, a wireless video camera system with an LCD monitor, and a rugged protective case assembly.



### SPECIFICATIONS

|                       |  |
|-----------------------|--|
| WEIGHT:               | 20 lbs.  |
| DIMENSIONS:           | 18.5" L x 7.25" W x 10.25" H                                     |
| POWER CONSUMPTION:    | 100 W  |
| OPERATING DISTANCE:   | 25–300 feet  |
| COMPATIBILITY:        | Eaton/Cutler-Hammer POW-R-WAY lineup of 100–200 A busway systems |
| CONTROL/POWER SOURCE: | CBS ArcSafe® RSO-I AR  |

### OVERVIEW

- Remote operation from up to 300 feet away
- Lightweight and portable for hard-to-access areas
- Simple setup; no equipment modification required
- Reduces or eliminates need for arc-flash hazard suits
- Designed, manufactured, and assembled in the USA

*Distance is Safety*  
**CBSArcSafe.com**

2616 SIRIUS ROAD, DENTON, TX 76208 | INFO @ CBSARC SAFE .COM

(472-3389)  
**(877) 4-SAFETY**

