

# OS Q1

The new dimension of book scanning



 **ZEUTSCHEL**  
WE DIGITIZE YOUR WORLD

# OS Q1

## The new dimension of book scanning

The OS Q Scanner Generation is the result of new technological developments as well as our consistent work on technical innovations. It fulfills the highest demands under the headings of image quality, process efficiency and productivity.

The unique image quality of the OS Q is based on the perfect interplay of especially high-quality technical components. Thus, the image quality of the OS Q extends far beyond the requirements of all common digitalization standards, e.g. ISO 19264, Metamorfoze or FADGI.

The scanning system features a completely new and self-developed camera system based on a CMOS sensor. The camera features a high dynamic range and is also capable of reproducing the finest gradations.

The result: sharp, low-noise, high-contrast images which reflect even the finest details true to the original.

A special guided lighting of the LED lighting system with a constant angle enables the OS Q to reproduce even difficult originals free from reflection or shadowing. Reflections on shining surfaces or shadows in the book fold are optically corrected.

A CRI value of over 97 combined with optimally matched camera and lighting components enable excellent color rendering. The OS Q sets the reference mark for high scanning productivity.

The OS Q Book Scanner series achieves the highest efficiency in the scanning process through the perfect interplay with tried and

tested Zeutschel imaging systems. Functions such as self-opening glass panes, sliding self-balancing book supporting plates and a scanning automatic system ensure the highest productivity levels.

The OS Q Book Scanner is designed as a flexible modular system. If the requirements and tasks increase, it can be expanded in a modular way.

Both an optical zoom and a macro lens for imaging small-format originals can be added as additional accessories. In addition, the settings of the OS Q can be adjusted to the task at hand. For example, lighting time and aperture can be set variably.





LED lighting system for reflection-free and shadow-free results

Perfect interplay between high-quality technical components

Ergonomic work method for the highest quality demands

OT 160-H35 XL




Completely new developed camera system based on a CMOS sensor

Wide range of interchangeable imaging systems

## Product advantages

- RGB line sensor  
(3-channel, CMOS technology)
- Resolution of up to 600 ppi
- Fulfills ISO 19264 / Quality Level A, Full Metamorfoze and FADGI\*\*\*\*
- Internal image processing with 96 bit depth
- Data output in 48 bit/24 bit color and 16 bit/8 bit degree
- True RGB capture on each pixel (no color interpolation)
- Color rendering index of LED lighting
- True parallel scanning
- Camera link interface for fastest image transfer
- Optical zoom (optional)
- Variable lighting times and aperture settings
- Interchangeable lenses including macro lens
- Imaging systems for a wide range of formats
- OmniScan software with 48 bit data output
- Focused line lighting for glare-free operation
- Fastest scanning speed
- Perfect Book – 3D scan technology for perfect book fold correction
- Parallel scanning and saving process based on 64 bit technology and multi-threading
- Scanning in both directions, forwards and backwards
- High productivity based on ROI scan function (limitation of the area to be scanned)
- Color rendering corresponds to the original
- No UV/IR radiation
- No reflections with high-shine originals
- Ergonomic work method with or without glass plate



- LED lighting system for reflection-free and shadow-free results




- Completely new developed camera system based on a CMOS sensor



- Perfect interplay between high-quality technical components



- Wide range of interchangeable imaging systems



- Fulfills ISO 19264 / Quality Level A, Full Metamorfoze and FADGI\*\*\*\*



- Optional: optical zoom

## Technical data

## OS Q1

Camera Sensor	RGB line sensor (3-channel, CMOS technology)
Resolution	9 LP / mm at 600 ppi (up to 12 LP / mm with zoom option)
Recording system	wear-free mechanical shutter, variable exposure time, electronically adjustable shutter; automatic white and black balance, variable depth of focus
Max. original size	924 mm x 700 mm
Max. book thickness	with book cradle OT 180 H 35 XL – 35 cm with book cradle OT 180 H 50 XL – 50 cm
Scan unit	CMOS RGB sensor
Scan mode	color: 96 bit / output 48 bit / 24 bit Grayscale: 32 bit / output 16 bit
Scanning speed (from start to end of scanning process) in A1	200 ppi – 3.5 sec. 400 ppi – 5.9 sec. 600 ppi – 7.6 sec.
Scanner interface	Camera Link
Zoom (optional)	A1 – A2 A1 – A3 (including extra lens)
Resolution	100 – 600 ppi
<b>Electrical data / safety</b>	
Voltage	110 – 240 V
Frequency	50 – 60 Hz
Max. consumption	440 W
<b>Safety inspections / authorizations</b>	- Authorization in accordance with the IEC agreement (international authorization for the safety of IT products – includes EMC, electrical safety, device safety for CE, UL, ETL, CSA) - LEDs tested in accordance with: IEC 62471:2006 “Photobiological safety of lamps and lamp systems”
<b>Dimensions</b>	
Width	1,370 mm
Depth (scanner including imaging system)	2,200 mm
Height	2,144 mm
<b>Imaging systems</b>	OT 180 H50 XL, OT 180 H35 XL, OT 180 H, OT 180, AT 1, OT 90, vacuum table
Accessories for imaging systems	Kit 90°, bookend 110° – 140°
<b>Recommended working conditions</b>	
Temperature range	18 – 35 °C
Relative air humidity, non-condensing	80 %
<b>Operating System</b>	
Operating system	Windows 10 64 bit
Scanning software	min. OmniScan OS 12.12 64 bit

Technical changes reserved



240.215.0224  
info@thecrowleycompany.com  
www.thecrowleycompany.com



More information:



www.zeutschel.com