

# Ultraviolet Water Purifier Comparison Chart

## FEATURES

S = Standard • O = Optional • ✓ = Yes

**Bio-Logic®**  
Pure Water Pack™  
1.5 GPM



**MINIPURE®**  
1 to 9 GPM



**Ultimate®**  
4 to 9 GPM



**MIGHTY★PURE®**  
3 to 20 GPM



**SANITRON®**  
3 to 416 GPM



**MEGATRON®**  
90 to 450 GPM



	<b>316</b>	<b>304</b>	<b>304</b>	<b>316</b>	<b>316</b>	<b>316</b>
Chamber Material (Stainless Steel Type)	<b>316</b>	<b>304</b>	<b>304</b>	<b>316</b>	<b>316</b>	<b>316</b>
<b>STER-L-RAY®</b> Germicidal Ultraviolet Lamp with 10,000 Hours Rated Effective Life	<b>S</b>	<b>S</b>	<b>S</b>	<b>S</b>	<b>S</b>	<b>S</b>
Quick Lamp Change with <b>EASY-OFF™</b> End Cap	<b>S</b>	<b>S</b>	—	<b>S</b>	<b>S</b>	<b>S</b>
<b>CRYSTAL CLEAR™</b> Quartz Sleeve	<b>S</b>	<b>S</b>	<b>S</b>	<b>S</b>	<b>S</b>	<b>S</b>
Lamp Out Indicator Light(s)	<b>S</b>	<b>S</b>	—	—	—	<b>S</b>
Sight Port to View Lamp Operation	—	—	<b>S</b>	<b>S</b>	<b>S</b>	<b>S</b>
Drain Fitting	—	—	—	<b>S</b>	<b>S</b>	<b>S</b>
Dual Action Wiper Mechanism	—	—	—	—	<b>Manual</b>	<b>Manual or Automatic</b>
Suggested Mount Installation	<b>Horizontal</b>	<b>Horizontal</b>	<b>Vertical</b>	<b>Horizontal</b>	<b>Horizontal</b>	<b>Horizontal</b>
Removable or Rotatable Heads	<b>S</b>	—	—	—	<b>S</b>	<b>S</b>
Alternate Inlet/Outlet Fittings	—	—	—	—	<b>O</b>	<b>O</b>
Sediment and Carbon Filter	<b>S</b>	—	—	—	—	—
<b>Promate™</b> Mounting Kit / Bracket	<b>S</b>	<b>S</b>	<b>S</b>	<b>O</b>	<b>O</b> ①	—
<b>GUARDIAN™</b> Ultraviolet Monitor	—	—	—	<b>O</b>	<b>O</b>	<b>S</b>
<b>SENTRY™</b> Safety Sensor	<b>O</b>	<b>O</b>	—	<b>O</b>	<b>O</b>	—
<b>Promate™</b> Audio Alarm	<b>S</b>	<b>S</b>	<b>S</b>	<b>O</b>	<b>O</b>	—
<b>Promate™</b> Solenoid Valve	—	<b>O</b>	—	<b>O</b>	<b>O</b>	—
<b>SureFLO™</b> Flow Control Valve	—	<b>O</b>	<b>S</b>	<b>O</b>	<b>O</b>	—
<b>Promate™</b> Elapsed Time Indicator	<b>O</b>	<b>O</b>	—	<b>O</b>	<b>O</b>	<b>S</b>
<b>Promate™</b> Time Delay Mechanism	—	<b>O</b>	—	<b>O</b>	<b>O</b>	—
Residential Use	✓	✓	✓	✓	✓	—
Commercial Use	—	—	—	✓	✓	✓
Industrial Use	—	—	—	—	✓	✓
<b>NSF</b> Certified Models	—	—	—	✓ ②	✓ ③	—

① **SANITRON®** Model S10,000C through S25,000C come equipped with mounting rack.

② **MIGHTY★PURE®** MP36C and MP49C are available with NSF®/ANSI 55 for Disinfection Performance, Class B.

③ **SANITRON®** Models S37C, S50C, and S2400C are certified to NSF®/ANSI 61 & 372. Model S2400C is used in modular form to build larger models.

• When used as directed to disinfect clear water, Atlantic Ultraviolet Corporation® water purifiers provide an ultraviolet dosage in excess of 30,000 micro-watt seconds per square centimeter (µWSec/cm2).

• This list depicts options for 120v 50/60Hz operation. Consult factory for options with other power requirements.



375 Marcus Boulevard  
Hauppauge, NY 11788  
631.273.0500 • Fax: 631.273.0771  
E-mail: Sales@AtlanticUV.com  
Ultraviolet.com • BuyUltraviolet.com