



DESCRIPTION

The **CBS ArcSafe® RRS-3 FlashGard** single-application remote racking system (RRS-3) is designed to operate the Eaton FlashGard motor control center (MCC) with no modification to existing electrical equipment, thanks to CBS ArcSafe's magnetic latching system. The lightweight, portable RRS-3 FlashGard allows technicians to remotely install and remove an MCC while standing up to 300 feet away. The RRS-3 FlashGard is compatible with the Cutler-Hammer/Eaton Intelligent Technologies (IT) MCC. Typical applications for the FlashGard MCC include the oil and gas, waste and wastewater, and mining industries. Designed, manufactured, and assembled in the United States, all RRS-3 units are portable, fast, and easy to set up; offer mechanical and/or electrical safety protection; are adjustable to fit unique electrical equipment configurations; reduce the requirements for personal protection equipment; and help customers with NFPA 70E arc-flash safety compliance. Optional features include 25-foot extension cables, a 24 V DC LED light, a wireless video camera system with an LCD monitor, and a rugged protective case assembly.

SPECIFICATIONS

WEIGHT:	18 lbs.
DIMENSIONS:	11.5"H x 70"W x 15"D
POWER CONSUMPTION:	50 W
OPERATING DISTANCE:	Up to 300 ft. away via radio remote
COMPATIBILITY:	Cutler-Hammer/Eaton Intelligent Technologies (IT), Eaton FlashGard motor control center
CONTROL/POWER SOURCE:	CBS ArcSafe® RSO-IV RR



OVERVIEW

- Remote operation from up to 300 feet away
- Lightweight and portable for hard-to-access areas
- Simple setup; no equipment modification required
- Reduces or eliminates need for arc-flash hazard suits
- Designed, manufactured, and assembled in the USA

